

EUROBOND IS A LIQUID APPLIED, LOW VISCOSITY BITUMEN SOLUTION.

Eurobond is used to prime concrete, brickwork and blockwork prior to the application of Euroseal membranes and other bitumen coatings.

1. APPLICATIONS

- Roofs
- Floor Slabs
- Tunnels
- Internal Wet Areas
- Basements

2. COST BENEFITS

- Highly penetrative. Strengthens porous substrates.
- Simple and rapid application.
- Over coat in 2 hours in ventilated conditions.
- Provides Temporary waterproofing until subsequent coatings are applied.

3. TYPICAL PHYSICAL & PERFORMANCE DATA

Form	Black Liquid
Solvent Type	Aromatic Hydrocarbon
Specific Gravity	0.90
Overcoat Time	2 - 4 hours
Non Volatile Content	55%
Maximum Service Temperature	80° c

4. INSTALLATION**Substrates**

- New concrete, screed or render should have a brushed or wood float finish, and should be free from contamination by any material which could impair adhesion. All surface defects should be repaired by approved methods. Protrusions greater than 3 mm should be removed.
- Existing concrete, screed or render should be well prepared to provide a dense, defect free substrate.
- Brickwork, blockwork and masonry should be flush pointed.
- All substrates should be dry.

Application

Apply using a wide nylon brush, sheepskin disposable rollers or airless spray. The product must not be applied in wet conditions. Clean tools using white spirit or Hydrocarbon solvent.

Coverage Rates

Dense Concrete	0.125 litres/m ²
Porous Concrete	0.25 litres/m ²
Lightweight Screed	0.5 litres/m ²



euro

POLYMERS GB

All products should be sold in accordance with the manufacturer's instructions. No responsibility can be taken by the manufacturers where conditions of use are beyond our control. Euro Polymers products are available for sale in accordance with Euro Polymers standard conditions of sale which are available on request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us or our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of the supplied product

euroPOLYMERSGB Wychwood House, 34 Low Hall Road, Horsforth, Leeds LS18 4EF

Tel: 0113 259 0777 • Fax: 0113 259 1010 • info@europolymers-gb.com • www.europolymers-gb.com